Text Align

2630 GstarCAD MY /KW November 11, 2021 Workflow 0 768

As the name describes, this function is used to align text. You can select several texts in your drawing to align along X or Y coordinates, or along a line of specific direction. You can access it from:

Menu: Text >Text Align

Command Entry: Textalign

For example, when we create a table or part list and some contents are not in the correct location, using this tool improves the efficiency of adjusting text. After the command is started, a message will display>

Please select object:

Then select the text(s) to be aligned:

After selecting the text(s), a message will display > Select the align method: X axis (X) / Y axis (Y) / Two points (P):

In this case, we choose the Y axis align method and then specify a point to align the texts in the correct location. The result is as follows:

8	.,						-0		_			
				7	BMW-C-	7 THR	EADED SHAF	FT.	1	Q235A		Weided ITEM 8
				6	BMW-C-	6	BUSHING 16		2	Q235A		Welded ITEM 5
d				5	BMW-C-	5 31	PPORTPLA	TE	1	STEEL		10,5mm. thickness
TEXTALI G TEXTALIGN			4	BMW-C-	4	BUSHING 'A'	•	1	Q235A		Welded ITE M S	
			3	BMW-C-	3 BMW-1	THREADED P	AN "8"	1	Q235A		M12×1,4×104	
			2	BMW-C-	2 BMW-	THREADED P	"A" 18	1	Q235A		M10 x2,5 x100	
				1	BMW-C-	1	TILT PLATE		1	STEEL		15mm. thickness
Please select object:	2209.7	836	< 2°	ITEM	PART NO		DESCRIPTION		aty.	MATERIAL	TREATMENT	REMARKS
						PA	RTS LIST					
0	INIT	400			ATE							~ ~ ~
•	INIT	АРР		-	ATE	APPROVALE		Gs	F	arC	D 2	013
•	INIT ARP	Alon	ROVALS so Pizzeli	•	ATE			Gs	ta	ar <mark>C/</mark>	\D 2	013
•		APP	ROVALS so Pizzali-		ATE		DATE	GS	ta	ar <mark>C/</mark>	D 2	013
ø		Aloni	ROVALS				DATE	NTLE				
ø		App	ROVALS so Pizzali		ATE		DATE	В	M٧	V CHA	ND 2	
ø		App	ROVALS so Pizzali		ATE		DATE	NTLE	M٧	V CHA		AMP

After selecting the text(s), a message will display > Select the align method: X axis (X) / Y axis (Y) / Two points (P):

In this case, we choose Y axis align method and then specify a point to align the texts in the correct location. The result is as follows:

	_		PARTS LIST						
Select the align method	Y	INIT		DATE	APPROVALS	DATE	6-1-		
		ARP	Alonso Pizzali				Gsta	r <mark>CAD</mark> 2013	
↓ ×							BMW	CHASSIS CLAMP	
Specify align point: 153.3589	< 164°						SIZE CAGE CODE	BWMCP-10006394	
							SCALE	SHEET	

In another example, we choose the X axis alignment method and then specify a point to align the texts in the correct location (end point of Leader). The result is as follows:



And finally, if we choose the Two points (P) alignment method and then specify two points to align the texts in the correct location (start and end point of Leader). The result is as follows:

Select the align m	nethod 🔳 P		
Specify first point:	148.0726 < 68°		
Specify second point:	52.0444 < 319°		Main pool
			Tourist Hotel
park 1	Main pool	park	Long Flume
	Tourist Hotel		
	Long Flume	park	Landscape sketch
part P P P P P P P P P P	Landscape sketch	N N N N N N N N N N N N N N N N N N N	

Online URL: https://www.gstarcad.com.my/knowledge/article/text-align-2630.html